

WKI-1001 1/2 H.P. SUBMITTAL SHEET

- · Space saving compact design!
- High-speed 2600 r.p.m. permanent magnet motor produces more power per pound.
- · Corrosion resistant grinding components.
- Fast and easy mount system provides a no hassle installation.
- · Removable splash guard is included.
- · Safe for properly sized septic tanks.



Connector sized for 7/8" I.D. / 22mm I.D. rubber hose. 12 1/4" 322mm Measurements are in inches / mm *Add 5/8" / 16mm or RFI Filter

SPECIFICATIONS	
Motor Horsepower	1/2 H.P.
Motor Speed R.P.M.	2600
Voltage	100, 110-130, 220-240, 220-240 CE, 220-240 BEAB
Hz	50/60
Amps - Watts	520W (100) 4.5 (110-130), 2.25 (220-240), 475W (220-240 BEAB)
Motor Type	Permanent Magnet
Sink Flange	Stainless Steel & Celcon
Stopper	Positive Seal
Splash Guard	Removable
Waste Elbow	ABS
Feed	Continuous
Grind Ring	Heavy Gauge Galvanized Steel
Swivel Impellers	Stainless Steel
Turntable	Galvanized Steel
Hopper	Glass Filled Nylon
Grinding Chamber	Corrosion Proof Glass Filled Polyester
Bearings	Permanently Lubricated; Sleeve Type
Overload Protector	Manual Reset Type
Shipping Weight (lbs.)	8.1
Pallet Quantity	196

Due to continued product improvement, system configurations and specifications may change without notice.



25300 Al Moen Dr. North Olmsted, OH 44070 (800) 854-3229 anaheimmfg.com