

## WKI-5000TC 3/4 H.P. SUBMITTAL SHEET

- · Batchfeed operation...No wall switch required!
- High-speed 2700 r.p.m. permanent magnet motor produces more power per pound.
- · Stainless steel grinding components.
- Fast and easy mount system provides a no hassle installation.
- · Safe for properly sized septic tanks.



| DIMENSIONS  |  |
|---|--|
| Knock-out for dishwasher drain<br>connector sized for 7/8" I.D. / 22mm I.D.<br>rubber hose. |  |
| 8 ½" 216m  9 ½" 238m  14 ½" 114m  422m  15 ½" 141m  Measurements are in inches / mm         |  |

\*Add 5/8" / 16mm for RFI Filter

| SPECIFICATIONS         |  |  |
|------------------------|--|--|
| Motor Horsepower       | 3/4 H.P.   |  |
| Motor Speed R.P.M.     | 2700   |  |
| Voltage                | 100, 110-130, 220-240, 220-240 CE, 220-240 BEAB                  |  |
| Hz                     | 50/60  |  |
| Current-Amps           | 720W (100), 6.0 (110-130), 3.0 (220-240),<br>520W (220-240 BEAB) |  |
| Motor Type             | Permanent Magnet   |  |
| Power Cord             | Attached   |  |
| Sink Flange            | Stainless Steel & Celcon   |  |
| Stopper/Actuator       | 3 Position   |  |
| Waste Elbow            | ABS  |  |
| Feed                   | Batch Loading  |  |
| Grind Ring             | Stainless Steel  |  |
| Swivel Impellers       | Cast Stainless Steel   |  |
| Turntable              | Stainless Steel  |  |
| Hopper                 | Glass Filled Nylon   |  |
| Grinding Chanber       | Corrosion Proof Glass Filled Polyester                           |  |
| Bearings               | Permanently Lubricated; Sleeve Type                              |  |
| Overload Protector     | Manual Reset Type  |  |
| Sound Shell            | Yes-Full   |  |
| Shipping Weight (lbs.) | 14   |  |
| Pallet Quantity        | 75   |  |

Due to continued product improvement, system configurations and specifications may change without notice.



25300 Al Moen Dr. North Olmsted, OH 44070 (800) 854-3229 anaheimmfg.com